

Ref:

NEBULADQ-SF-WH-27W-3K


Item No: NEBULA SURFACE – 12376

orlight[®]
FROM SOURCE TO SITE

NEBULADQ-SF-200 is a UGR<19, surface mounted downlight, constructed from Aluminium which provides a downward directional light distribution. This downlight features a high lumen output and CRI >85 for light quality assurance. The product is supplied with a 60° optic as standard. Emergency option available. Please note: the driver and emergency inverter are integral to the fitting.



DIMENSIONS



OPTICAL PERFORMANCE

Wattage	27W
Lumen Output	2700LM
Efficacy	100LM/W
CCT	3000K
CRI	CRI > 85
Binning	2 STEP MACADAMS
Beam Angle	60°
UGR	UGR < 19
Chipset	CITIZEN LED CHIPSET
Calculated Chip Life	L70 > 105,000HRS

ELECTRICAL

Constant Current or Voltage	CONSTANT CURRENT
Voltage	36V
Milliamp / Current	700MA
Driver Configuration	INTEGRAL
Control	SWITCHED

CONSTRUCTION

Installation	SURFACE
Construction	ALUMINIUM
Diameter	210 MM
Height	220 MM
Weight	3.32KG
Tilt	FIXED
Finish	WHITE
RAL	RAL 9016
IP Rating	IP20
Operating Ambient Temperature	-20°C - +35°C

EMERGENCY

Emergency	AVAILABLE
Emergency Configuration	INTEGRAL

NEBULADQ-SF-WH-27W-3K

Item No: NEBULA SURFACE – 12376

LIGHT DISTRIBUTION

