

Ref:

# LUNEX-1200-36W-3K-DALI-B-EM

Item No: LUNEX – 41676

**orlight**<sup>®</sup>  
FROM SOURCE TO SITE

The LUNEX-1200 is a premium 36W DALI-B-EM 3K linear LED tubular light designed for commercial interiors and architectural lighting schemes. This model is supplied as a non-linkable fixture. Its sleek form and high-efficiency output deliver wide 120° illumination with excellent visual comfort. A PMMA diffuser and 316L stainless steel end caps offer a refined, modern aesthetic. Ideal for offices, clean zones, and exposed ceilings in contemporary environments. Supplied with a Quick-Fit surface bracket; suspension kit available separately. Featuring integral emergency.



## DIMENSIONS



## OPTICAL PERFORMANCE

|                      |                  |
|----------------------|------------------|
| Wattage              | 36W              |
| Lumen Output         | 5508LM           |
| Efficacy             | 153LM/W          |
| CCT                  | 3000K            |
| CRI                  | CRI > 80         |
| Beam Angle           | 120°             |
| Chipset              | ORLIGHT LED      |
| Calculated Chip Life | L70 > 100,000HRS |

## ELECTRICAL

|                             |                  |
|-----------------------------|------------------|
| Constant Current or Voltage | CONSTANT CURRENT |
| Voltage                     | 240V             |
| Milliamp / Current          | 255MA            |
| Driver Configuration        | INTEGRAL         |
| Control                     | DALI DIMMABLE    |

## CONSTRUCTION

|                               |                     |
|-------------------------------|---------------------|
| Installation                  | SURFACE / SUSPENDED |
| Construction                  | PMMA                |
| Diameter                      | 72MM                |
| Length                        | 1200 MM             |
| Finish                        | STAINLESS STEEL     |
| IP Rating                     | IP66                |
| IK Rating                     | IK06                |
| Operating Ambient Temperature | -20°C - +40°C       |

## EMERGENCY


|                         |                |
|-------------------------|----------------|
| Emergency               | YES            |
| Emergency Configuration | INTEGRAL       |
| Emergency Duration      | EMERGENCY 3HRS |
| EM Lumen                | 472LM          |

# LUNEX-1200-36W-3K-DALI-B-EM

Item No: LUNEX – 41676

**orlight**<sup>®</sup>  
FROM SOURCE TO SITE

## LIGHT DISTRIBUTION



## ADDITIONAL PRODUCT IMAGES



## FIXING DETAILS



## SUSPENSION KIT



**999-ORLALP018-R-SW**

13781

Suspension Kit