


Ref:

GRAFIK3-WH-2700K

Item No: GRAFIK – 11278

orlight[®]
FROM SOURCE TO SITE


Orlight's Grafik range is a perfect combination of lens and reflectors. This recessed LED downlight is constructed from Aluminium, available in a variety of colour temperatures and CRI>90 provides light quality assurance. Finished in white with optional order only reflectors to suit your aesthetical requirements. Please Note: This product does not support hot plugging. Orlight does not recommend cutting of holes prior to receipt of product in hand.



UGR
< 19

IP20

DIMENSIONS



OPTICAL PERFORMANCE

Wattage	9W
Lumen Output	504LM
Efficacy	56LM/W
CCT	2700K
CRI	CRI > 90
Binning	2 STEP MACADAMS
Beam Angle	40°
UGR	UGR < 19
Chipset	OSRAM LED
Calculated Chip Life	L70 > 105,000HRS

ELECTRICAL

Constant Current or Voltage	CONSTANT CURRENT
Voltage	10V
Milliamp / Current	700MA
Driver Configuration	REMOTE
Control	SWITCHED

CONSTRUCTION

Installation	RECESSED
Construction	ALUMINIUM
Length	98 MM
Width / Depth	45 MM
Height	58 MM
Cutout	89 MM X 35 MM
Tilt	FIXED
Finish	WHITE
RAL	RAL 9016
IP Rating	IP20
Operating Ambient Temperature	-20°C - +35°C

EMERGENCY


Emergency	AVAILABLE
Emergency Configuration	REMOTE

GRAFIK3-WH-2700K


Item No: GRAFIK – 11278

orlight[®]
FROM SOURCE TO SITE


LIGHT DISTRIBUTION




COMPATIBLE REFLECTORS



GRAFIK3-RF-GL
11275
Grafik Pod Reflector



GRAFIK3-RF-MT
11276
Grafik Pod Reflector



GRAFIK3-RF-WH
11277
Grafik Pod Reflector