

Ref:

ORL1009-SF-85-BL

Item No: ORL1009 – 12921

orlight[®]
FROM SOURCE TO SITE

Surface mounted architectural downlight, featuring an anti-glare baffle and magnetic lamp change mechanism. Finished in Black RAL9005 or White RAL9016, with a choice of light sources available. Orlight does not recommend cutting of holes prior to receipt of product in hand.



DIMENSIONS

OPTICAL PERFORMANCE

LOR	56
-----	----

ELECTRICAL

Driver Configuration	REMOTE (LED ENGINE)
----------------------	---------------------

CONSTRUCTION


Installation	SURFACE
Construction	ALUMINIUM
Diameter	88 MM
Height	85 MM
Weight	0.465KG
Tilt	FIXED
Finish	BLACK
RAL	RAL 9005
IP Rating	IP20
Compatible Light Source	GU10 / ENGINE
Lamp Change	MAGNETIC MECHANISM

EMERGENCY

Emergency	AVAILABLE
Emergency Configuration	REMOTE

ORL1009-SF-85-IP20

FIXED



ORL1009-SF-85-BL

Item No: ORL1009 – 12921

orlight[®]
FROM SOURCE TO SITE

COMPATIBLE GU10 LAMP



LX4 - SWITCHED



LX5 - MAINS DIMMABLE

COMPATIBLE LED ENGINE



DB6-R999



DB8-R999



DB8-F-R999



DB11-R999



DB13-R999