

Ref:

CL-RCT-BL-3M-DALI

Item No: CROSSLINE – 10528

orlight[®]
FROM SOURCE TO SITE

The Recessed/Trimless DALI Track is designed for Orlight's CROSSLINE range. Crafted with precision from durable aluminium, this track is elegantly finished in Black RAL9005. The magnetic strip ensures a secure placement for Power Feeds and Flexible Continuous Connectors. Note: For all straight tracks of the CROSSLINE range, END CAPS are required at BOTH ENDS, even when using 'L' shape Connectors.



ELECTRICAL

Voltage	48V
Control	DALI DIMMABLE

CONSTRUCTION

Installation	RECESSED TRACK
Construction	ALUMINIUM
Length	3000 MM
Width / Depth	56 MM
Height	52 MM
Finish	BLACK
RAL	RAL 9005
IP Rating	IP20

DIMENSIONS



CL-RCT-BL-3M-DALI

Item No: CROSSLINE – 10528

POWER FEED



CL-BL-PF-500MM-DALI
17743
Power Feed With 500mm Cable



CL-BL-PF-2000MM-DALI
17746
Power Feed With 2000mm Cable


CONNECTORS



CL-RCT-LVC
17756
Vertical "L" Shape Connector Kit



CL-RCT-LOC
17755
Outer "L" Shape Connector Kit



CL-RCT-BL-LHC
17754
"L" Shape Horizontal Connector Kit



CL-BL-FC-DALI
17742
Flexible Continuous Connector



CL-BL-MLC
17739
Mechanical Linear Connector

BLANKING PLATE




CL-BC-BL-1M
17744
Recessed Blanking Cover

CL-RCT-BL-3M-DALI

Item No: CROSSLINE – 10528

orlight[®]
FROM SOURCE TO SITE

END CAPS



CL-RCT-BL-EC

10529

Recessed End Caps

SWITCHED DRIVER (REMOTE)



ORLRPV48100

15246

48V Switched Driver



ORLRPV48-150-HLG-A

15247

48V Switched Driver