

Ref:

LUCIA500-SB-WH-3K4K-EM

Item No: LUCIA – 11847

orlight[®]
FROM SOURCE TO SITE


Architectural surface fixture constructed from Stainless Steel to IP54. Solid State chipset with downward light emission and wide beam distribution. Integral power supply unit available in switched, 1-10V and DALI dimmable configurations. Light quality assurance with CRI >80. Please Note: This product does not support hot plugging.



SWITCHABLE
CCT

IP54

DIMENSIONS



OPTICAL PERFORMANCE

Wattage	23W
Lumen Output	1606LM / 1670LM
Efficacy	70LM/W / 73LM/W
CCT	3000K/4000K
CRI	CRI > 80
Binning	2 STEP MACADAMS
Beam Angle	120°
Chipset	SOLID STATE SMD
Chip Life	L70 > 50,000HRS

ELECTRICAL

Constant Current or Voltage	CONSTANT CURRENT
Voltage	240V
Milliamp / Current	500MA
Driver Configuration	INTEGRAL
Control	SWITCHED

CONSTRUCTION

Installation	SURFACE MOUNTED
Construction	STAINLESS STEEL
Length	500 MM
Width / Depth	145 MM
Height	90 MM
Weight	2.95KG
Finish	WHITE
RAL	RAL 9016
IP Rating	IP54
Operating Ambient Temperature	-40°C - +55°C

EMERGENCY


Emergency	YES
Emergency Configuration	INTEGRAL
Emergency Duration	EMERGENCY 3HRS
EM Lumen	209LM / 217LM

LUCIA500-SB-WH-3K4K-EM

Item No: LUCIA – 11847

orlight®
FROM SOURCE TO SITE

LIGHT DISTRIBUTION



PLEASE NOTE:

This product does not support hot plugging